

Product Details

Eaves Protection Strip is a specially cut 500mm or 330mm width of high performance polyester based roofing (BS 747 Type 5U) designed to give long term protection where dressing an underslating felt into an external half round gutter. It can be used with any underslating materials (including breather membranes), any tile or slate finishes and in cold or warm roof configurations. The use of this material is recommended by BS 5534: 2003, Code of practice for slating and tiling.

- Purpose-made eaves protection starter strip
- Tailor made roll size
- Durable – will last the life of the roof covering
- Universal – can be used with all types of underslating
- Rot-proof – will not deteriorate, even when wet for long periods



Application

Eaves Protection Strip is fixed as the first sheet along the eaves, so it can be subsequently dressed over and inside the edge of the external gutter. The main underslating sheets should then be laid horizontally up the roof from that point.

When installing underslating, vertical laps should be a minimum of 100mm and should be supported over a rafter. Horizontal laps will vary depending on the pitch of the roof and should be formed in accordance with the table set out below:

Reinforcing strips of 600mm minimum should be fixed at hips, ridges and valleys.

If used during the winter months should be stored between 10°C and 20°C for 24 hours prior to use and not applied at temperatures below 5°C. If applied at temperatures below 10°C the membrane should be warmed gently with a hot air gun at details that involve folding.

Dimensions

Length:	16m
Width:	500mm/330mm
Weight:	14.5kg

Roof Pitch Horizontal Lap

12.5° – 14°	225mm
15° - 34°	150mm
35° and above	100mm